



drapilux GmbH • 48282 Emsdetten • Hansestraße 87
Postfach • 48270 Emsdetten
Telefon 02572 / 927 - 0 • Fax 02572 / 927445
www.drapilux.com • e-mail: info@drapilux.com
Box 1243 • 48270 Emsdetten Germany
Tel: +49 2572 927 - 0 • Fax: +49 2572 927 - 483
www.drapilux.com • export@drapilux.com

drapilux

drapilux 240/241 flammstop



240 08



240 07



240 04



240 14



240 03



240 13



240 02



240 12



240 01



240 18



240 17



240 27



240 28



240 05



240 38



240 15



240 25



240 35



240 06




240 16



241 08



241 18



241 04



241 14



241 03



241 13



241 02



241 12



241 01



241 07



241 17



241 27



241 28



241 05



241 38



241 15



241 25



241 35



241 06



241 16

Technische Daten:

DIN 4102 B 1
M 1 Non Feu (B+F+E)
Classe 1 (I)
BS 5867 (GB)
EN 13 773 Classe 1
IMO Res. A.471 (XII)

Material: 100% Polyester (Trevira CS)



ca. 300 cm
ca. 260 g/m²

Rapport: ↔ ca. 2 cm drapilux 240

Rapport: ↔ ca. 31 cm drapilux 241

Martindale ca. 20.000 T.

DIN EN ISO 12947-2

Pilling note 4-5

DIN EN ISO 12945-2



flammstop



akustik



Ab 150 m auch in jeder Sonderfarbe lieferbar!

minimum quantity for special colours: 150 r.m.

quantité minimale pour des teintures spéciales: 150 m.l.

quantita minima per colori speciali: 150 mtl.

drapilux