

Breeze Fusion

Colour 2426-04931

Colour scale



Please be aware that the colour shades can appear different from the real fabric colours. We advise you to request actual fabric samples before ordering.

Design no. 2426 Breeze Fusion (140 cm/55") is available in 44 colours



Breeze Fusion is a richly textured, woollen upholstery fabric brought to life by intriguing colour blends that merge across the surface creating a vibrant, contemporary expression full of complexity and mystery. The surprising colour combos invite you to explore the infinite shades and nuances undulating across the graphic surface. As the colours are constantly changing depending on the light and perspective, it is an endless journey.

Meets Möbelfakta requirements

Design and colours are developed by Cenk Kivrikoglu

Order

Please sign in to
order fabrics and
samples.



Product specifications

Characteristics

Design no.

2426 — Breeze Fusion

Application

Upholstery

Composition

88% New Zealand wool, 12% Polyamide

Weight

590 g/lm — 19.03 oz/lin.yd

Width

140 cm — 55 inches

Environment

Environment, health, and safety

OEKO-TEX® STANDARD 100

EU Ecolabel

Meets Möbelfakta requirements

VOC emission

Ansi/Bifma VOC test M7.1

Performance

Abrasion

100,000 — rubs martindale (EN ISO 12947-2)

100,000 — rubs martindale (ASTM D4966) (heavy duty upholstery)

Pilling

4-5 — scale 1-5, max. 5 (EN ISO 12945-2)

Light fastness

5-7 — scale 1-8, max. 8 (EN ISO 105-B02)

Rubbing fastness dry/wet

4-5/4-5 — scale 1-5, max. 5 (EN ISO 105x12)

Flammability

BS 5852 Part 1 0,1 Cigarette & Match, The Furniture and Furnishing Regulations 1988

BS EN 1021 1&2 Cigarette and Match CA TB 117-2013

ASTM E84 Class 2(Unadhered)

Class Uno UNI 9175 Class 1 I EMME

AM 18 - NF D 60-013-(only for fabric)

IMO EC Declaration of Conformity EU,UK

IMO MSC 307(88) Annex 1 part 8

IMO MSC 307(88) Annex 1 part 8 UK

MED Certificate IMO

MED Certificate IMO UK

BS 5852 Crib 5 (option flame retardant)

Will also pass other flammability

standards. Flame retardant performance is dependent upon the foam used. Contains no flame retardant chemicals.

US ACT pass

 [ASTM D4966 Martindale \(heavy duty\)](#)

 [ASTM D4970 Pilling](#)

 [AATCC 16 Light fastness](#)

 [AATCC 8 or 116 Dry/wet crocking](#)

 [CA TB 117-2013](#)

 [ASTM E84 Class 2\(Unadhered\)](#)

Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Certificates

Acoustic test sound absorption

Test	Condition	No.	Date	Download
ISO 354 & ISO 11654 (sound absorption)		B104146/67	08 Nov 2024	PDF

Abrasion resistance

Test	Condition	No.	Date	Download
BS EN ISO 12947-2/14465	In accordance with EN 14465	144444148	17 Sep 2026	PDF
ASTM D4966 Martindale		26-003187	02	PDF

(heavy duty)

Oct
2026

Pilling

Test	Condition	No.	Date	Download
BS EN ISO 12945-2		144444148	17 Sep 2026	PDF
ASTM D4970 Pilling		26-002571	20 Aug 2026	PDF

Colour fastness to light

Test	Condition	No.	Date	Download
BS EN ISO 105 B02 Method 2		62756-01	06 May 2014	PDF
BS EN ISO 105 B02 Method 2		1011671953a	18 Nov 2018	PDF
BS EN ISO 105 B02 Method 2		2026AN2395	17 Sep 2026	PDF
AATCC 16 Light fastness		2026AN2196	31 Aug 2026	PDF

Dry and wet rubbing/crocking

Test	Condition	No.	Date	Download
BS EN ISO 105-X12 Rubbing dry/wet		2026AN2532	22 Sep 2026	PDF
BS EN ISO 105-X12 Rubbing		28510042-	30	PDF

dry/wet		a002	Oct 2018	
AATCC 8 or 116 Dry/wet crocking		2026AN2197	22 Sep 2026	PDF
Flammability				
Test	Condition	No.	Date	Download
BS 5852 Part 1 0,1 Cigarette & Match, The Furniture and Furnishing Regulations 1988	20-22 kg/m3 non- fire retardant polyurethane foam	93305	03 Jan 2018	PDF
BS EN 1021 1&2 Cigarette and Match	20-22 kg/m3 non- fire retardant polyurethane foam	93305-01	04 Jan 2018	PDF
CA TB 117-2013		26-002571	21 Aug 2026	PDF
ASTM E84 Class 2(Unadhered)	Unadhered	3-54181-0	20 Dec 2023	PDF
Class Uno UNI 9175 Class 1 I EMME		232535 / 1	30 May 2017	PDF
AM 18 - NF D 60-013-(only for fabric)		2022AN1263	23 Sep 2022	PDF
IMO EC Declaration of Conformity EU,UK			11 Sep 2026	PDF
IMO MSC 307(88) Annex 1 part 8		SH01671	09 Jan 2025	PDF
IMO MSC 307(88) Annex 1		53163	09	PDF

part 8 UK

Jan
2025

MED Certificate IMO

SH01685

07 [PDF](#)
Feb
2025

MED Certificate IMO UK

53166

07 [PDF](#)
Feb
2025

Flammability with flameretardant treatment

Test	Condition	No.	Date	Download
BS 5852 Crib 5 (option flame retardant)	35 kg/m3 CMHR foam		11 Dec 2024	PDF

Colour fastness to dry cleaning

Test	Condition	No.	Date	Download
BS EN ISO 105-D01		93305-02	09 Jan 2018	PDF

Colour fastness to water spotting

Test	Condition	No.	Date	Download
BS EN ISO 105-E16		93305-02	09 Jan 2018	PDF

Colour Fastness to Perspiration

Test	Condition	No.	Date	Download
BS EN ISO 105-E04		93305-02	09 Jan 2018	PDF
AATCC 15 Perspiration		3-29296-5	15	PDF

Nov
2018

Rubbing with organic solvents

Test	Condition	No.	Date	Download
BS EN ISO 105-D02 Organic solvents		93305-02	09 Jan 2018	PDF

Seam slippage

Test	Condition	No.	Date	Download
BS EN ISO 13936-2		103603	16 Jan 2019	PDF
ASTM D4034 Yarn slippage at a sewn seam		3-29296-4	14 Nov 2018	PDF

Breaking Force

Test	Condition	No.	Date	Download
ASTM D5034 Breaking force		3-29296-3	14 Nov 2018	PDF

VOC emission

Test	Condition	No.	Date	Download
Ansi/Bifma VOC test M7.1		392-2025-00560701	02 Dec 2025	PDF

Material Safety Data Sheet

Test	Condition	No.	Date	Download
Material Safety Data Sheet			30	PDF