

SPECIFICATIONS

Physical Properties:

Weight	U.S. Units	Metric Units
	20.0 oz./LY	612 G/LM
	13.2 oz./SY	442 G/SM
Backing Material:	Non-Woven	
Material Width	52/54"	132/137 cm

Federal Specifications:

APEX Vinyl Wallcoverings meet or exceed all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings. This product has been accepted for use by the City of New York Dept. of Buildings under MEA-381-93M.

Fire Hazard Classification Results:

ASTM E-84 Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 10
 PASS rating as tested under NFPA 286 (Corner burn test)
 CAN/ULC 5102-10 Fire Test: Class A, Flame Spread: 22; Smoke Developed: 25
 EN 13501-1 Fire Classification: B-s2, d0

Performance Features:

- Orth-Phthalate Free
- Aluminum trihydrate fire retardant (antimony-free)
- Ultra-Fresh[®] antimicrobial (non-arsenic)
- No heavy metals or formaldehyde
- Printed exclusively with water-based, low VOC inks
- Roller applied AQUA-CLEAR 3.0™ top finish for improved stain resistance
- Microventing for permeability is available on a custom order basis
- Advanced Warning Effect (ionization-type smoke detector)
- Five-year warranty against materials defects; Consult your distributor for details

Environmental Attributes:

- Ultra-low emitting; Pass rating under CA 01350
- Listed on state of California CHPS (Collaborative for High Performing Schools)
- SCS Indoor Advantage™ Gold building product Indoor air quality certified to SCS-EC10.3-2014/ v. 3.0
- Conforms to CDPH/ EHLB standard method v. 1.1, 2010
- NSF/ANSI 342 Sustainability Standard – Silver Qualified Manufacturer
- CA Prop 65 compliant
- Published Health Product Declaration (HPD) – LEED eligible

Permeability, Moisture and Mold:

To reduce the risk of fungal growth it is recommended that all APEX wallcovering(s) be microvented when installed in Humid climates. Please contact your Distributor for more information.

AQUA-CLEAR 3.0™ is a proprietary top finish of Len-Tex Corporation.

Ultra-Fresh™ is a registered trademark of Thomson Research Associates Inc.

