

TECHNICAL INFORMATION

**Physical properties**

Total weight: 460g/m² (nominal)
 Vinyl Weight: 400g/m² (nominal)
 Substrate Type: Polycotton Osnaburg
 Fabric Backing
 Substrate weight: 60g/m² (nominal)
 Tensile Strength: MD 40 N/cm (nominal)
 TD 30 N/cm (nominal)
 Tear Strength: 4500 mN (nominal)

**Roll size:**

137cm x 27.4m - cut lengths available

**Fire Rating:**

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7). Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

**Adhesive:**

Fabric backed vinyls - Newmor Heavy. Varies with substrate - please enquire.

**Bacteria Resistance:**

Contains an active Fungicide.

**Light Fast:**

Excellent Light Fastness
 BS EN ISO 105-B02 7/8

Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WA - Quality Standard W-101.

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test. Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth. Please allow 5/7 days for delivery.

Origin:

Designed, coloured, manufactured and stocked in the USA.

Warranty:

Newmor offers a five year warranty against manufacturing defects. Full details available on application.

Samples:

Larger samples are readily available on request

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine releasing agent solutions.



FM 23833



British Product Global Support



Newmor
 WALLCOVERINGS

UK SALES:
 T: 01938 551990
 E: sales@newmor.com

EXPORT SALES:
 T: + 44 (0) 1938 55 2671
 E: enquires@newmor.com