

TECHNICAL INFORMATION

Physical properties

Total weight: 400g/m²

Vinyl Weight: 310g/m²

Substrate Type: Non-Woven Fabric

Substrate weight: 90g/m²

Type II and other specifications available

Tensile Strength: MD 40 N/cm (nominal)

TD 30 N/cm (nominal)

Tear Strength: 4500 mN (nominal)

Roll size:

127cm x 30m - cut lengths available

Fire Rating:

Class 'O' to the requirements of Approved

Document B of the British Building

Regulations (Class 1, BS 476 part 7).

Euroclass B - s2, d0. Class A ASTM E-84

Tunnel Test.

Adhesive:

Fabric backed vinyls - Newmor Heavy.

Varies with substrate - please enquire.

Bacteria Resistance:

Contains an active Fungicide.

Light Fast:

Excellent Light Fastness

BS EN ISO 105-B02 min. 7/8

LRV = Light reflective value

Specifications

Conforms to requirements of BS EN 15102,
BS EN 259 and WA - Quality Standard W-101.

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.

Resistant to temporary staining of oils,
fats, mild acids and alkalis.

Quality Assurance:

All management systems and production
procedures comply with ISO 9001, the
internationally recognised Quality
Standard.

Availability:

Orders are usually dispatched within
7-10 days from approval of your samples

Origin:

Designed, coloured and manufactured in
the UK.

Warranty:

Newmor offers a five year warranty
against manufacturing defects.

Full details available on application.

Samples:

Larger samples are readily available on
request.

Maintenance:

The digital image is printed with UV Cured inks and care must be
taken not to damage the image with harsh cleaning products, nylon
scourers and brushes etc.

The image should be cleaned by using a non-foaming detergent di-
luted with warm water and a soft cloth. We recommend cleaning
from the skirting upwards. This should avoid runs of dirty water
staining the surface.

To avoid re-activating the adhesive, which could cause edges to lift,
care should be taken not to over-wet the joins or to allow water to
pool at skirting levels.

Once washed, rinse with clean water and dry by dabbing with soft
towelings.

Under no circumstances should spirit based cleaners be used as
these will degrade the vinyl base and remove the printing inks.

