

TECHNICAL INFORMATION

**Physical properties**Total weight: 400g/m² (nominal)Vinyl Weight: 360g/m² (nominal)Substrate Type: 100% Woven Cotton
- Cotton ScrimSubstrate weight: 40g/m² (nominal)**Other specifications available**

Tensile Strength: MD 40 N/cm (nominal)

TD 30 N/cm (nominal)

Tear Strength: 4500 mN (nominal)

**Roll size:**

130cm x 30m - cut lengths available

**Pattern Repeat**

Free match

**Fire Rating:**

Class 'O' to the requirements of Approved Document B of the British Building Regulations. Eurocalss B - s2, d0.

Class A ASTM E-84 Tunnel Test.

**Adhesive:**Fabric backed vinyls - Newmor Heavy.
Varies with substrate - please enquire.**Bacteria Resistance:**

Contains an active Fungicide.

**Light Fast:**

Excellent Light Fastness

BS EN ISO 105-B02 min 6

LRV = Light reflective value

SpecificationsConforms to requirements of BS EN 15102,
BS EN 259 and WA - Quality Standard W-101.**Stain/Chemical Resistance:**

Pass ASTM D-1308-1987 Federal Spot Test.

Resistant to temporary staining of oils,
fats, mild acids and alkalis.**Quality Assurance:**Our management system and production
procedures comply with ISO 9001: 2015,
the internationally recognised Quality
Standard.**Availability:**

Every product stocked in depth.

5.00pm deadline for next day delivery.
(UK only)**Origin:**Designed, coloured, manufactured and
stocked in the UK.**Warranty:**Newmor offers a five year warranty
against manufacturing defects.

Full details available on application.

Samples:Larger samples are readily available on
request.**Maintenance:**Fully washable and in most cases products
can be scrubbed repeatedly to remove any
marks without damaging the product itself.
Also able to withstand the use of chlorine
releasing agent solutions.

Customise this design



youchoose™

Our Unique Re-Colouration Service

www.newmor.com

British Product | Global Support

**Newmor**
WALLCOVERINGS**UK SALES:**

T: 01938 551990

E: sales@newmor.com**EXPORT SALES:**

T: + 44 (0) 1938 55 2671

E: enquires@newmor.com