

TECHNICAL INFORMATION

Physical properties

Total weight: 460g/m² (nominal) Vinyl Weight: 355g /m² (nominal) Substrate Type: Non Woven Fabric

Substrate weight: 105g/m² (nominal) Other specifications available

Tensile Strength: MD 80 N/cm (nominal) TD 60 N/cm (nominal) 8500 mN (nominal)

Tear Strength:



130cm x 30m cut lengths available

Pattern Repeat 53cm repeat

random match (to best finish)

Fire Rating:

Class 'O" to the requirements of Approved Document B of the British Building Regulations. Euroclass B -s1, d0. Class A ASTM E-84 Tunnel Test.

Adhesive:

P

Fabric backed vinyls - Newmor Heavy. Varies with substrate - please enquire.

Bacteria Resistance:

Contains an active Fungicide.

Light Fast:

Excellent Light Fastness BS EN ISO 105-B02 min. 6

Light reflective value (LRV)

In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

JAK 001 12

Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WA - Quality Standard W-101.

Stain/Chemical Resistance:

Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management system and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth. 5.00pm deadline for next day delivery. (UK only)

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects. Full details available on application.

Samples:

Larger samples are readily available on request

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine releasing agent solutions.







UK SALES: T: 01938 551990 E: sales@newmor.com

EXPORT SALES: T: + 44 (0) 1938 55 2671 E: enquirires@newmor.com