

## TECHNICAL INFORMATION



### Physical properties

Total weight: 675g /m<sup>2</sup> (nominal)

Vinyl Weight: 635g /m<sup>2</sup> (nominal)



Substrate Type: 100% Woven Cotton-Cotton Scrim

Substrate weight: 40g/m<sup>2</sup> (nominal)

### Type II other specifications available

Tensile Strength: MD 40 N/cm (nominal)

TD 30 N/cm (nominal)

Tear Strength: 4500 mN (nominal)



### Roll size:

130cm x 20m - cut lengths available



### Pattern Repeat

N/A,

random match



### Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations. Euroclass B -s2, d0.

Class A ASTM E-84 Tunnel Test.



### Adhesive:

Fabric backed vinyls - Newmor Heavy.

Varies with substrate - please enquire.



### Bacteria Resistance:

Contains an active Fungicide.



### Light Fast:

Excellent Light Fastness

BS EN ISO 105-B02 min. 6

### Light reflective value (LRV)

In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

STUD 01 55

STUD 02 49

STUD 03 35

STUD 04 22

STUD 05 82

STUD 06 52

STUD 07 29

STUD 08 24

STUD 09 79

STUD 10 52

STUD 11 46

STUD 12 21

STUD 13 68

STUD 14 43

STUD 15 14

STUD 16 4

### Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WA - Quality Standard W-101.

### Stain/Chemical Resistance:

Resistant to temporary staining of oils, fats, mild acids and alkalis.

### Quality Assurance:

Our management system and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

### Availability:

Every product stocked in depth.  
5.00pm deadline for next day delivery.  
(UK only)

### Origin:

Designed, coloured, manufactured and stocked in the UK.

### Warranty:

Newmor offers a five year warranty against manufacturing defects.  
Full details available on application.

### Samples:

Larger samples are readily available on request.

### Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Also able to withstand the use of chlorine releasing agent solutions.

Customise this design 

**youchoose**<sup>™</sup>

Our Unique Re-Colouration Service

[www.newmor.com](http://www.newmor.com)



**Newmor**  
WALLCOVERINGS

UK SALES:  
T: 01938 551990  
E: [sales@newmor.com](mailto:sales@newmor.com)

EXPORT SALES:  
T: + 44 (0) 1938 55 2671  
E: [enquires@newmor.com](mailto:enquires@newmor.com)