



Decor Design Centre

Castello Product Specifications

“a dynamic tipped effect, offering depth and distinction in every colour”

CASTELLO PRODUCT INFORMATION:

Type: Semi Aniline (Tipped effect)
Source: Italy
Average Hide Size: 5.0m²
Thickness: 1.0 - 1.1mm

CASTELLO is a distinguished leather produced on premium European cow hides. CASTELLO is immediately identifiable by its distinctive tipped effect, with the peaks of the grain being darker than the base leather colour. This creates a sophisticated and unique appearance in a protected semi-aniline leather, making CASTELLO an ideal selection for all interior environments.

The colours in CASTELLO are contemporary, yet timeless. They invite the designer to make the leather the anchor of a scheme and to build further tones and textures to complement this beautiful leather.

All colours are in stock in our warehouse and available for immediate delivery.

Custom colours are available on request.

COMPANY ENVIRONMENTAL NOTES:

CASTELLO is produced in Italy by an ISO 14001 certified company. The tannery also carries the ISO 9001 Quality Certification.

The tannery manages all production, laboratory and effluent processes in-house, employing a full time chemist to oversee the process and ensure the tannery adheres to the most progressive standards and industry-leading processes. The tanning group has been at the centre of Environmental reform in the industry and is one of few tanneries to operate its own water purification plant. The tannery has received industry awards for its environmental processes and water treatment quality.

CASTELLO is produced using only water-based dyes.

All tannery wastage (liquid, gas and solid) is treated according to European Standards on-site and again at a shared off-site facility.

Detailed product and tannery environmental notes are available on request.

| Test | Normative | Unit | Value |
|--|-------------|----------------|----------------------|
| THICKNESS | ISO2589 | mm | 0.9/1.1mm |
| TEAR STRENGTH | ISO3377-2 | N/mm | 20N min |
| ADHESION | ISO 11644 | N/cm | >2 N/cm min |
| COLOUR FASTNESS - ARTIFICIAL LIGHT | ISO 105-B02 | 72 hr | 5 min (Blue Scale) |
| FLEX RESISTANCE | ISO 5402 | 50000 cycles | No Cracks |
| COLOUR FASTNESS TO RUBBING | ISO 11640 | 500 cycles dry | 4 min (Grey Scale) |
| | | 80 cycles wet | 3/4 min (Grey Scale) |
| BURNING BEHAVIOUR TO CIGARETTE & MATCH FLAME | ISO 1021-1 | | PASS |
| COLOUR FASTNESS TO WATER SPOTTING | ISO 105-E07 | | 3 min (Grey Scale) |

Decor Design Centre
 185 Hay Street, Subiaco
 Western Australia 6008
 +61 8 9328 1077
 info@decordesign.com.au
 www.decordesign.com.au
 @ decordesigncentre