

STEP MELANGE SCREEN


COLOUR 2307-62544



Please be aware that the colour shades can appear different from the real fabric colours. We advise you to request actual fabric samples before ordering.

COLOUR SCALE

Design no. 2305/2306/2307 Step Melange Screen (170 cm/67") is available in 24 colours



Step Melange Screen is made from 100% Trevira CS polyester and is perfect for workplace and public areas with strict fire and safety regulations. Step Melange Screen is designed for innovative room division solutions – from screens and panels to privacy pods. The fabric also comes in a uni-coloured version, Step Screen. The colours of Step Melange Screen and Step Screen harmoniously complement each other as well as the colour palettes of upholstery textiles Step and Step Melange.

Meets Möbelfakta requirements

Designed by: Gabriel Design Team
Colours designed by: Maria Wolff Metternich



PRODUCT SPECIFICATIONS

CHARACTERISTICS

Design no.

2305 / 2306 / 2307 — Step Melange Screen

Application

Screen

Panel

Composition

100% Trevira CS

Weight

440 g/lm — 14.19 oz/lin.yd

Width

170 cm — 67 inches

PERFORMANCE

Light fastness

6-8 — scale 1-8, max. 8 (EN ISO 105-B02)

Rubbing fastness dry/wet

4-5/4-5 — scale 1-5, max. 5 (EN ISO 105x12)

FLAMMABILITY

Certificates

[BS EN 1021 1&2 Cigarette and Match](#)

[DIN 4102 - B1](#)

[DIN EN 13501-1 B-s1,d0\(glued\)](#)

[DIN EN 13501-1 B-s1,d0](#)

[NF P 92-503/504/505 M1](#)

[Class Uno UNI 9175 Class 1 I EMME](#)

[Class Uno UNI 8456 - UNI 9174](#)

[Class Uno UNI 8457 - UNI 9174](#)

Will also pass other flammability standards.

Flame retardant performance is dependent upon the foam used.

CERTIFICATES

ACOUSTIC TEST AIR FLOW RESISTANCE

Test	Condition	No.	Date	Download
EN 29053 & ISO 9053-1 (airflow resistance)		B104146/65	16 May 2023	PDF

COLOUR FASTNESS TO LIGHT

Test	Condition	No.	Date	Download
BS EN ISO 105 B02 Method 2		2023AN6191	27 Jun 2023	PDF

DRY AND WET RUBBING/CROCKING

Test	Condition	No.	Date	Download
BS EN ISO 105-X12 Rubbing dry/wet		2023AN6270	15 Sep 2023	PDF

FLAMMABILITY

Test	Condition	No.	Date	Download
BS EN 1021 1&2 Cigarette and Match	35 kg/m3 CMHR foam	23/61004/05/23	16 May 2023	PDF
DIN 4102 - B1		230142	14 Mar 2023	PDF
DIN EN 13501-1 B-s1,d0(glued)		23AN1145	30 May 2023	PDF
DIN EN 13501-1 B-s1,d0		Z-56.25-3573	09 Oct 2023	PDF
NF P 92-503/504/505 M1		230492	21 Jun 2023	PDF
Class Uno UNI 9175 Class 1 I EMME		230492	21 Jun 2023	PDF
Class Uno UNI 8456 - UNI 9174		LSFIRE/NC19085/00000/01	07 May 2024	PDF
Class Uno UNI 8457 - UNI 9174		LSFIRE/NC19085/00000/01	07 May 2024	PDF

VOC EMISSION

Test	Condition	No.	Date	Download
Ansi/Bifma VOC test M7.1		961098-C	24 Jan 2024	PDF

RESISTANCE TO BLEACH CLEANING

Test	Condition	No.	Date	Download
Internal test according BIFMA HCF 8.1 and ACT Method 1	1:10 Sodium Hypochlorite 5,25-6,25%		21 Aug 2023	PDF

MATERIAL SAFETY DATA SHEET

Test	Condition	No.	Date	Download
Material Safety Data Sheet			31	PDF

ENVIRONMENTAL DATA

Test	Condition	No.	Date	Download
LCA Summary Report			11 Nov 2024	PDF

CARE & MAINTENANCE

Wiping down with water.

Step Melange Screen is made of Trevira CS which is a polyester material suited for environments with special requirements for cleaning.

Click here for guidance relating to disinfection. [Link to Stain Guide...](#)
